

MARINER MX DATA SHEET

MX62 SST

TECHNICAL SPECIFICATIONS

MX62 SST

SKU 93617 - White | 93616 - Black

UOM Each

Tweeter 1" (25mm) cloth dome, Ferrofluid-cooled, acoustic back chamber, dual voice coil

Woofer 6.5" (165mm) textured polypropylene cone, rubber surround, dual voice coil

Dispersion Technology Sinusoidal Textured Waveguide

Frequency Response 55Hz-20Hz +/-3dB

Impedance 8 ohms nominal; 6 ohms minimum

Power Handling 5 Watts minimum; 125 Watts maximum

Sensitivity 89dB SPL (2.83V/1 meter)

Environmental Mill Spec 810 for humidity, salt spray, temperature, UV; IP66 waterproof rating

Environmental Temp -13° to 149°F (-25°C to 65°C)

Grille Material Perforated aluminum


Color White (RAL 9003) or Black (RAL 7021)

Dimensions without Bracket (WxHxD) 7.56" x 12.15" x 7.32" (192mm x 308.5mm x 186mm)

Dimensions with Bracket (WxHxD) 7.56" x 12.95" x 7.83" (192mm x 329mm x 199mm)

Shipping Weight 7lbs (3.2kg) each

DIMENSIONAL DRAWINGS



7.56" (192mm)




7.32" (186mm)





7.83" (199mm)



7.56" (192mm)

Front View Side View Bracket Back View Bracket Side View

Bracket Back View

LIMITED FIVE (5) YEAR WARRANTY Sonance warrants to the first end-user purchaser that this Sonance-brand product ("Product"), when purchased from an authorized Sonance Dealer/Distributor, will be free from defective workmanship and materials for the period stated above. Sonance will at its option and expense during the warranty period, either repair the defect or replace the Product with a new or remanufactured Product or a reasonable equivalent. For more details please refer to the product manual.

©2024 Sonance. All rights reserved. Sonance is a registered trademarks of Dana Innovations. Due to continuous product improvement, all features and specifications are subject to change without notice. For the latest Sonance product specification information visit our website at www.sonance.com.