



## SPECIFICATIONS

<b>Description:</b>	2-way full-range speaker for wall placement
<b>Power handling:</b>	250 W (IEC)
<b>Tweeter:</b>	1 x 28mm / 1.1" Fabric soft dome
<b>Midrange/woofer:</b>	2 x 180 mm / 6.5", aluminum cone, 35 mm voice coil, vented magnet, vented die-cast aluminum basket
<b>Frequency response:</b>	45 – 20.000 Hz (-3dB)
<b>Enclosure:</b>	Bass reflex port, downfiring (40 Hz), MDF construction, internally braced
<b>Nominal impedance:</b>	4 Ohm (min. 3.7 Ohm)
<b>Maximum SPL:</b>	117 dB (1m, peak)
<b>Sensitivity:</b>	92 dB (2.83V/1m)
<b>Crossover point:</b>	2.2 kHz
<b>Connections:</b>	Binding posts, gold plated
<b>Recommended placement:</b>	Floor standing, against the wall
<b>Dimensions (W x H x D):</b>	32.5 x 102.4 x 16 cm (height including required feet) 12.8 x 40.3 x 6.3 inches (height including required feet)
<b>Weight:</b>	18.0 kg / 39.7 lb
<b>Standard finishes</b> (enclosure/front baffle):	White/white, black/black, mocca/mocca, white/black, white/mocca, black/mocca
<b>Optional front baffles:</b>	White, black, mocca
<b>Optional fabric covers:</b>	Midnight grey, grey
<b>Accessories:</b>	Wall mount kit